


Automata & languages

A primer on the Theory of Computation



Laurent Vanbever
www.vanbever.eu

ETH Zürich (D-ITET)
October, 19 2017

Part 5 out of 5

Last week was all about

Context-Free Languages

Context-Free Languages


a superset of Regular Languages

Example $\{0^n 1^n \mid n \geq 0\}$ is a CFL but not a RL


As for Regular Languages,
Context-Free Languages are recognized by “machines”

Language	Regular	Context-Free
Machine	DFA/NFA	PDA

Push-Down Automatas are pretty similar to DFAs




Push-Down Automatas are pretty similar to DFAs
except for... **the stack**




Language $L = \{a^i b^j c^k \mid i, j, k \geq 0 \text{ and } i=j \text{ or } i=k\}$

Machine (PDA)



This week, we'll see that computers are not limitless

Alan Turing (1912-1954)



Some problems
cannot be solved
by a computer
(no matter its power)

But before that, we'll prove some extra properties about Context-Free Languages

Today's plan
Thu Oct 20

- 1 PDA \approx CFG
- 2 Pumping lemma for CFL
- 3 Turing Machines

Even smarter automata...


- Even though the PDA is more powerful than the FA, it is still **really** stupid, since it doesn't understand a lot of important languages.
- Let's try to make it more powerful by adding a **second stack**
 - You can push or pop from either stack, also there's still an input string
 - Clearly there are quite a few "implementation details"
 - It seems at first that it doesn't help a lot to add a second stack, but...

Even smarter automata...

- Even though the PDA is more powerful than the FA, it is still **really** stupid, since it doesn't understand a lot of important languages.
- Let's try to make it more powerful by adding a **second stack**
 - You can push or pop from either stack, also there's still an input string
 - Clearly there are quite a few "implementation details"
 - It seems at first that it doesn't help a lot to add a second stack, but...
- Lemma: A PDA with two stacks is **as powerful as** a machine which operates on an infinite tape (restricted to read/write only "current" tape cell at the time – known as "Turing Machine").
 - Still that doesn't sound very exciting, does it...?!?

Automata & languages

A primer on the Theory of Computation



Part 3

regular
language

context-free
language

turing
machine

Turing Machine

- A **Turing Machine (TM)** is a device with a finite amount of *read-only* “hard” memory (states), and an unbounded amount of read/write tape-memory. There is no separate input. Rather, the input is assumed to reside on the tape at the time when the TM starts running.
- Just as with Automata, TM’s can either be input/output machines (compare with Finite State Transducers), or yes/no decision machines.

2/3

Turing Machine: Example Program

- Sample Rules:
 - If read 1, write 0, go right, repeat.
 - If read 0, write 1, HALT!
 - If read □, write 1, HALT! (the symbol □ stands for the blank cell)
- Let’s see how these rules are carried out on an input with the *reverse* binary representation of 47:

1	1	1	1	0	1				
---	---	---	---	---	---	--	--	--	--

2/4

Turing Machine: Formal Definition

- Definition: A **Turing machine** (TM) consists of a 7-tuple $M = (Q, \Sigma, \Gamma, \delta, q_0, q_{acc}, q_{rej})$.
 - Q, Σ , and q_0 , are the same as for an FA.
 - q_{acc} and q_{rej} are accept and reject states, respectively.
 - Γ is the tape alphabet which necessarily contains the blank symbol \bullet , as well as the input alphabet Σ .
 - δ is as follows:
$$\delta : (Q - \{q_{acc}, q_{rej}\}) \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$$
 - Therefore given a non-halt state p , and a tape symbol x , $\delta(p,x) = (q,y,D)$ means that TM goes into state q , replaces x by y , and the tape head moves in direction D (left or right).

2/5

Turing Machine: Formal Definition

- Definition: A **Turing machine** (TM) consists of a 7-tuple $M = (Q, \Sigma, \Gamma, \delta, q_0, q_{acc}, q_{rej})$.
 - Q, Σ , and q_0 , are the same as for an FA.
 - q_{acc} and q_{rej} are accept and reject states, respectively.
 - Γ is the tape alphabet which necessarily contains the blank symbol \bullet , as well as the input alphabet Σ .
 - δ is as follows:

$$\delta : (Q - \{q_{acc}, q_{rej}\}) \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$$
 - Therefore given a non-halt state p , and a tape symbol x , $\delta(p,x) = (q,y,D)$ means that TM goes into state q , replaces x by y , and the tape head moves in direction D (left or right).
- A string x is **accepted** by M if after being put on the tape with the Turing machine head set to the left-most position, and letting M run, M eventually enters the accept state. In this case w is an element of $L(M)$
 - the language accepted by M .

2/6

Comparison

Device	Separate Input?	Read/Write Data Structure	Deterministic by default?
FA	Yes	None	Yes
PDA	Yes	LIFO Stack	No
TM	No	1-way infinite tape. 1 cell access per step.	Yes (but will also allow crashes)

2/7


Turing Machine: Goals

- First Goal of Turing's Machine: A "computer" which is as **powerful** as any real computer/programming language
 - As powerful as C, or "Java++"
 - Can execute all the same algorithms / code
 - Not as fast though (move the head left and right instead of RAM)
 - Historically: A model that can compute anything that a human can compute. Before invention of electronic computers the term "computer" actually referred to a *person* who's line of work is to calculate numerical quantities!
 - This is known as the [Church-[Post-]] Turing thesis, 1936.
- Second Goal of Turing's Machine: And at the same time a model that is **simple** enough to actually prove interesting epistemological results.


2/8

Can a computer compute anything...?!?

- Given collection of dominos, e.g.



- Can you make a list of these dominos (repetitions are allowed) so that the top string equals the bottom string, e.g.




- This problem is known as Post-Correspondance-Problem.
- It is provably **unsolvable** by computers!

2/9

Also the Turing Machine (the Computer) is limited

- Similarly it is undecidable whether you can cover a floor with a given set of floor tiles (famous examples are Penrose tiles or Wang tiles)



- Examples are leading back to Kurt Gödel's incompleteness theorem
 - “Any powerful enough axiomatic system will allow for propositions that are undecidable.”



2/10


Decidability

- A **function is computable** if there is an algorithm (according to the Church-Turing-Thesis a **Turing machine** is sufficient) that computes the function (in finite time).

2/11

Decidability


- A **function is computable** if there is an algorithm (according to the Church-Turing-Thesis a **Turing machine** is sufficient) that computes the function (in finite time).
- A subset T of a set M is called **decidable** (or recursive), if the function $f: M \rightarrow \{\text{true}, \text{false}\}$ with $f(m) = \text{true}$ if $m \in T$, is **computable**.



2/12

Decidability

- A **function is computable** if there is an algorithm (according to the Church-Turing-Thesis a **Turing machine** is sufficient) that computes the function (in finite time).
- A subset T of a set M is called **decidable** (or recursive), if the function $f: M \rightarrow \{\text{true}, \text{false}\}$ with $f(m) = \text{true}$ if $m \in T$, is **computable**.
- A more general class are the **semi-decidable** problems, for which the algorithm must only terminate in finite time in either the true or the false branch, but not the other.



2/13

Halting Problem

- The halting problem is a famous example of an **undecidable** (semi-decidable) **problem**. Essentially, you cannot write a computer program that decides whether another computer program ever terminates (or has an infinite loop) on some given input.
- In pseudo code, we would like to have:

```
procedure halting(program, input) {  
  if program(input) terminates  
  then return true  
  else return false  
}
```

2/14

Halting Problem: Proof

- Now we write a little wrapper around our halting procedure

```
procedure test(program) {  
  if halting(program, program) = true  
  then loop forever  
  else return  
}
```

- Now we simply run: `test(test)` ! **Does it halt!?**

2/15

Excursion: P and NP

- **P** is the complexity class containing decision problems which can be solved by a Turing machine in time polynomial of the input size.

2/16

Excursion: P and NP

- **P** is the complexity class containing decision problems which can be solved by a Turing machine in time polynomial of the input size.
- **NP** is the class of decision problems solvable by a non-deterministic polynomial time Turing machine such that the machine answers "yes," if at least one computation path accepts, and answers "no," if all computation paths reject.

2/17

Excursion: P and NP


- **P** is the complexity class containing decision problems which can be solved by a Turing machine in time polynomial of the input size.
- **NP** is the class of decision problems solvable by a non-deterministic polynomial time Turing machine such that the machine answers "yes," if at least one computation path accepts, and answers "no," if all computation paths reject.
 - Informally, there is a Turing machine which can check the correctness of an answer in polynomial time.
 - E.g. one can check in polynomial time whether a traveling salesperson path connects n cities with less than a total distance d .

2/18

NP-complete problems

- An important notion in this context is the large set of **NP-complete** decision problems, which is a subset of NP and might be informally described as the "hardest" problems in NP.
- If there is a polynomial-time algorithm for even one of them, then there is a polynomial-time algorithm for **all** the problems in NP.
 - E.g. Given a set of n integers, is there a non-empty subset which sums up to 0? This problem was shown to be NP-complete.
 - Also the traveling salesperson problem is NP-complete, or Tetris, or Minesweeper.

2/19




P vs. NP

- One of the big questions in Math and CS: **Is $P = NP$?**
 - Or are there problems which cannot be solved in polynomial time.
 - Big practical impact (e.g. in Cryptography).
 - One of the seven **\$1M problems** by the Clay Mathematics Institute of Cambridge, Massachusetts.

2/21


Summary (Chomsky Hierarchy)




2/22

Bedtime Reading

If you're leaning towards "human = machine"



If you're leaning towards "human \supset machine"



2/23